

SPECIFICATIONS

Programmable DC Power Supply

MODEL : EX60 - 20TB



ODA

TECHNOLOGIES
www.odacore.com

Parameter		Specifications	
Output rating(@0℃ ~ 40℃)	Voltage	0 to 60.0	Maximum 63.0
	Current	0 to 20.0	Maximum 21.0
Output WATT		1.3 KW	
Programming Accuracy (@25℃ ± 5℃)± (%of output + offset)	Voltage	0.1% + 90.0mV	
	Current	0.1% + 60.0mA	
Readback Accuracy (@25℃ ± 5℃)± (%of output + offset)	Voltage	0.1% + 60.0mV	
	Current	0.1% + 40.0mA	
Ripple and Noise(20Hz to 20MHz)		≤ 10mVrms	
Load Regulation (with V- Sensing)		≤ 60 mV	
Line Regulation (with V- Sensing)		≤ 60 mV	
Resolution	Programming/Readback	≤ 1.5mV / ≤ 0.6mA	
	Display Meter	10mV / 10mA	
Temperature Coefficient After a 30- minute warm- up	Voltage	≤ 12.0mV	
	Current	≤ 6.0mA	
Stability ± (%of output + offset) After a 1 hour warm- up	Voltage	≤ 30.0mV	
	Current	≤ 10.0mA	
Voltage Programming Speed (10%~ 90% of output voltage)	Half load	Rising time	≤ 300ms
		Falling time	≤ 300ms
Remote Sensing Capability	Voltage Drop	Up to 2.5V per each lead	
	Load Regulation	Add 5 mV to spec for each 1- volt change in the + output lead due to load current changes	
	Load Voltage	Subtract voltage drop in load leads from specified output voltage rating.	
OVP and OCP Accuracy ± (%of output + offset)	OVP	1% + 0.6V	
	OCP	1% + 2.0A	
	Activation Time	< 80ms when maximum output rating	
Output Voltage Overshoot & Undershoot	Power Switch ON/OFF	No overshoot, undershoot : ≤ - 0.8V	
	Voltage Output Setting	No overshoot, No undershoot	
Remote Interface		RS232C , RS485 , USB Standard	
Programming Language		SCPI(Standard Commands for Programmable Instruments)	
Command Processing Time(average)	Apply	Setting	20ms
		Query	32ms
	Output Setting	Voltage & Current Setting	15ms
		Voltage & Current Query	32ms
	Measurement	Voltage & Current Query	32ms
The Other	Setting & Query	< 35ms	
State Storage Memory		Ten user- configurable(voltage,current,protection level)stored states	
Operation Temperature		0℃ ~ 40℃ for full rated output. At higher temperatures the output current is derated linearly to 50% at 55℃ maximum temperature	
Cooling		Isolation DC FAN	
Output Terminal Isolated (maximum, from chassis ground)		± 60 Vdc when connecting shorting conductors without insulation to the (+)output to the (+)sense and the (-)output and the (-)sense terminals	
AC Input Ratings	Standard	single phase 220V ± 10% 50~ 60Hz	
Calibration Interval	Precision	6 month	
	Recommended	1 year	
Dimensions (19" Standard)		265(W) * 75(H) * 404(D)	
Maximum Input Power(full load)		1.6 KW	
Weight	Net weight	6kg	
	Gross weight	7.5kg	

*상기모델은 사용자 Application에 최적화하기위해 예고없이 사양변경될 수 있으므로 구입전 확인하시기 바랍니다.