

SPECIFICATIONS

Programmable DC Power Supply

MODEL : OPE-920DI



ODA
TECHNOLOGIES
www.odacore.com

| Parameter | | | Specifications | |
|---|------------------------|--------------|--|-----------------|
| Output rating(@0℃ ~ 40℃) <i>Full channel isolated</i> | Channel 1 | | 0 to 9V / 0 to 20A | |
| | Channel 2 | | 0 to 9V / 0 to 20A | |
| Output WATT | | | 360W | |
| Programming Accuracy (@25℃ ±5℃)±(%of output + offset) | Voltage | | 0.2% + 100mV | |
| | Current | | 0.2% + 100mA | |
| Readback Accuracy (@25℃ ±5℃)±(%of output + offset) | Voltage | | 0.2% + 100mV | |
| | Current | | 0.2% + 100mA | |
| Ripple and Noise(20Hz to 20MHz) | Voltage | | ≤ 2mVp-p | |
| | Current | | ≤ 3mArms | |
| Load Regulation (@25℃ ±5℃)±(%of output + offset) | Voltage | | 0.01% + 2mV | |
| | Current | | 0.01% + 2mA | |
| Line Regulation (@25℃ ±5℃)±(%of output + offset) | Voltage | | 0.01% + 2mV | |
| | Current | | 0.01% + 2mA | |
| Resolution | Programming/Readback | | ≤ 3mV / ≤ 5mA | |
| | Display Meter | | 10mV / 100mA | |
| Temperature Coefficient ±(%of output + offset) After a 30-minute warm-up | Voltage | | 0.02% + 2mV | |
| | Current | | 0.05% + 8mA | |
| Stability ±(%of output + offset) After a 1 hour warm-up | Voltage | | 0.1% + 2mV | |
| | Current | | 0.2% + 8mA | |
| Transient Response Time | | | Less than 50μs for output to recover to within 15mV following a change in output current from full load to half load or vice versa | |
| Voltage Programming Speed (10% ~ 90%) | No load | Rising time | ≤ 120ms | |
| | | Falling time | ≤ 3.6s | |
| | Half load | Rising time | ≤ 120ms | |
| | | Falling time | ≤ 15ms | |
| Tracking Accuracy | | | 0.5% + 18mV | |
| Output Voltage Overshoot & Undershoot | Power Switch ON/OFF | | No overshoot, undershoot : ≤0V ~ ≥ -0.3V | |
| | Voltage Output Setting | | No overshoot, No undershoot | |
| Remote Interface | | | RS232C Standard (RS485 Option) | |
| Programming Language | | | SCPI(Standard Commands for Programmable Instruments) | |
| Command Processing Average Time (@19200bps) | Output Setting | | Voltage & Current Setting | 10ms |
| | | | Voltage & Current Query | 12ms |
| | Measurement | | Voltage & Current Query | 15ms |
| | | | The Other | Setting & Query |
| State Storage Memory | | | Five user-configurable(voltage,current)stored states | |
| Operation Temperature Range | | | 0℃ ~ 40℃ for full rated output. At higher temperatures the output current is derated linearly to 50% at 55℃ maximum temperature | |
| Cooling | | | Isolation DC FAN | |
| Output Terminal Isolated (maximum, from chassis ground) | | | ±30V output is ±60 Vdc when connecting shorting conductors without insulation between the (+),(-) output terminals and shassis. | |
| AC Input Ratings | Standard | | 220V ± 10% 50~60Hz | |
| | Option | | 100V ± 10% 50~60Hz | |
| | | | 110V ± 10% 50~60Hz | |
| | | | 230V ± 10% 50~60Hz | |
| Calibration Interval | | | Recommended 1 year | |
| Dimensions | | | Standard 426mm(W) * 177mm(H) * 505mm(D) 19-inch 4U Standard Size | |
| Maximum Input Power(full load) | | | 964W | |
| Weight | Net weight | | 18kg | |
| | Gross weight | | 19.2kg | |