

SPECIFICATIONS

Programmable DC Power Supply

MODEL : OPE-803DI



ODA
TECHNOLOGIES
www.odacore.com

Parameter			Specifications	
Output rating(@0℃ ~ 40℃) <i>Full channel isolated</i>	Channel 1		0 to 80V / 0 to 3A	
	Channel 2		0 to 80V / 0 to 3A	
Output WATT		480W		
Programming Accuracy (@25℃ ±5℃)±(%of output + offset)	Voltage		0.3% + 500mV	
	Current		0.2% + 15mA	
Readback Accuracy (@25℃ ±5℃)±(%of output + offset)	Voltage		0.3% + 500mV	
	Current		0.2% + 15mA	
Ripple and Noise(20Hz to 20MHz)	Voltage		≤ 3mVp-p	
	Current		≤ 2mArms	
Load Regulation (@25℃ ±5℃)±(%of output + offset)	Voltage		0.01% + 2mV	
	Current		0.01% + 500μA	
Line Regulation (@25℃ ±5℃)±(%of output + offset)	Voltage		0.01% + 2mV	
	Current		0.01% + 500μA	
Resolution	Programming/Readback		≤ 30mV / ≤ 1mA	
	Display Meter		100mV / 10mA	
Temperature Coefficient ±(%of output + offset) After a 30-minute warm-up	Voltage		0.02% + 10mV	
	Current		0.02% + 3mA	
Stability ±(%of output + offset) After a 1 hour warm-up	Voltage		0.1% + 5mV	
	Current		0.2% + 5mA	
Transient Response Time			Less than 50μs for output to recover to within 15mV following a change in output current from full load to half load or vice versa	
Voltage Programming Speed (10% ~ 90%)	No load	Rising time	≤ 70ms	
		Falling time	≤ 1.5s	
	Half load	Rising time	≤ 70ms	
		Falling time	≤ 10ms	
Tracking Accuracy			0.5% + 160mV	
Output Voltage Overshoot & Undershoot	Power Switch ON/OFF		No overshoot, undershoot : ≤0V ~ ≥ -0.3V	
	Voltage Output Setting		No overshoot, No undershoot	
Remote Interface			RS232C Standard (RS485 Option)	
Programming Language			SCPI(Standard Commands for Programmable Instruments)	
Command Processing Average Time (@19200bps)	Output Setting	Voltage & Current Setting		10ms
		Voltage & Current Query		12ms
	Measurement	Voltage & Current Query		15ms
	The Other	Setting & Query		32ms
State Storage Memory			Five user-configurable(voltage,current)stored states	
Operation Temperature Range			0℃ ~ 40℃ for full rated output. At higher temperatures the output current is derated linearly to 50% at 55℃ maximum temperature	
Cooling			Isolation DC FAN	
Output Terminal Isolated (maximum, from chassis ground)			±30V output is ±60 Vdc when connecting shorting conductors without insulation between the (+),(-) output terminals and shassis.	
AC Input Ratings	Standard	220V ± 10% 50~60Hz		
		100V ± 10% 50~60Hz		
	Option	110V ± 10% 50~60Hz		
		230V ± 10% 50~60Hz		
Calibration Interval	Recommended		1 year	
Dimensions	Standard		426mm(W) * 177mm(H) * 505mm(D) 19-inch 4U Standard Size	
	Option		300mm(W) * 150mm(H) * 465mm(D) Non Standard Small Size	
Maximum Input Power(full load)			861W	
Weight	Net weight		16kg	
	Gross weight		17.2kg	