

SPECIFICATIONS

MODEL : LF900-B(900W)



ODA

TECHNOLOGIES
www.odacore.com

Parameter		Specifications		
Operating range(@0°C ~ 40°C)	Voltage	1 to 300.0V	Maximum 315.0	
	Current	0 to 60.0A	Maximum 63.0	
	Max Power	0 to 900.0W at 40°C	(derated to 720.0W at 50°C)	
MODE SPECIFICATIONS				
CC MODE	RANGE	HI 0 to 63.0A LOW 0 to 6.0A		
	RESOLUTION	LOW 0.1mA	HI 1.0mA	
	Accuracy	±0.1%±12.0mA (after 30sec wait)		
CV MODE	RANGE	HI 1 to 315.0V LOW 0 to 40.0V		
	RESOLUTION	LOW 1.0mV	HI 10.0mV	
	Accuracy	±0.05%±60.0mV		
CR MODE	RANGE	0.1 to 3kΩ		
	RESOLUTION	100mΩ		
	Accuracy	±0.5%±200mΩ (<50mS)		
CP MODE	RANGE	0 to 900.0W at 40°C		
	RESOLUTION	100mW		
	Accuracy	±0.5%±200mW (<50mS)		
ON/OFF MODE	RANGE	0 to 63.0A		
	RESOLUTION	1.0mA		
	Accuracy	±0.1%±12.0mA (after 30sec wait)		
	ON/OFF TIME	100mS~250H59M59S990mS(10mS Unit)		
	REPEAT	1~65000		
FUSE MODE	RANGE	0 to 63.0A		
	RESOLUTION	1.0mA		
	Accuracy	±0.1%±12.0mA (after 30sec wait)		
	FUSE TIME	100mS~250H59M59S990mS(10mS Unit)		
BAT MODE	CC	RANGE	0 to 63.0A	
		Accuracy	±0.1%±12.0mA (after 30sec wait)	
	CR	RANGE	0.1 to 3kΩ	
		Accuracy	±0.5%±200mΩ (<50mS)	
	CP	RANGE	0 to 900.0W at 40°C	
		Accuracy	±0.5%±200mW (<50mS)	
	END Volt	0 to 315.0V		
END CAP	0.01 to 5000AH			
CYCLE MODE	CC	RANGE	0 to 63.0A	
		Accuracy	±0.1%±12.0mA (after 30sec wait)	
	CV	RANGE	0 to 315.0V	
		Accuracy	±0.05%±60.0mV	
	CYCLE TIME	100mS~250H59M59S990mS(10mS Unit)		
	STEP	1~100Step		
REPEAT	1~65000			
DYNAMIC MODE	MEMORY CH	2CH		
	Freq Range	0.5Hz ~ 10KHz		
	Freq Accuracy	3%		
	Duty Cycle Range	3~97%(<200μS)		
	Duty Cycle Accuracy	6% of setting±2%		
	CC	Range	0 to 63.0A	
		Accuracy	A ±0.1%±12.0mA	B ±0.2%±24.0mA
	CV	Range	0 to 315.0V	
		Accuracy	A ±0.05%±60.0mV	B ±0.1%±120.0mV
SLEW RATE(typical values: 5%~95%)				
CC,CR,CP MODE	<200uS(0 to 60.0A)			
CV MODE	<2mS(0 to 300.0V)			
PROTECTION				
OVP	324.0V(<10mS)			
OCP	64.8A(<10mS)			
OPP	972.0W(<10mS)			
OTP	100°C(Heatsink Temp)			
Short& Open	Shor	100mΩ(max), 50mΩ(typical)		
	Open	≥20kΩ		
Ripple& Noise	Current	4mA(rms)/40mA(p-p)		
	Voltage	6mV(rms)		
Remote Sensing	3Vdc between sense And load input			
INPUT AC	110/220V(S/W) ± 10% 50~60Hz/300mA POWER MAX :66W			
Remote Interface	RS-232C & RS-485 (TCP/IP Option)			
Cooling	Isolation DC FAN			
Dimensions (19-inch 2U Standard)	426mm(W) * 88mm(H) *470mm(D) (900~1200W)			
Weight	15kg(Net weight) / 16kg(Gross weight)			