

# SPECIFICATIONS

Programmable DC Power Supply

MODEL : OPM-95D



# ODA

TECHNOLOGIES  
www.odacore.com

Parameter		Specifications	
Output rating(@0℃ ~ 40℃)	Channel 1	0 to 9V / 0 to 5A	
	Channel 2	0 to 9V / 0 to 5A	
Output WATT		90W	
Programming Accuracy (@25℃ ±5℃)±(%of output + offset)	Voltage	0.05% + 5mV	
	Current	0.15% + 5mA	
Readback Accuracy (@25℃ ±5℃)±(%of output + offset)	Voltage	0.05% + 2.5mV	
	Current	0.08% + 3mA	
Ripple and Noise(20Hz to 20MHz)	Voltage	≤ 2mVp-p	
	Current	≤ 2mArms	
Load Regulation (with V-Sensing)	Voltage	≤ 2mV	
	Current	≤ 500μA	
Line Regulation (with V-Sensing)	Voltage	≤ 500μV	
	Current	≤ 500μA	
Resolution	Programming/Readback	≤ 80μV / ≤ 50μA	
	Display Meter	1mV / 100μA	
Temperature Coefficient ±(%of output + offset) After a 30-minute warm-up	Voltage	0.01% + 3mV	
	Current	0.02% + 3mA	
Stability ±(%of output + offset) After a 1 hour warm-up	Voltage	0.02% + 1mV	
	Current	0.1% + 1mA	
Transient Response Time		Less than 50μs for output to recover to within 15mV following a change in output current from full load to half load or vice versa	
Voltage Programming Speed	No load	Rising time	≤ 7.5V/ms
		Falling time	≤ 3V/ms
	Half load	Rising time	≤ 3.25V/ms
		Falling time	≤ 6V/ms
OVP and OCP Accuracy ±(%of output + offset)	OVP		5% + 0.1V
	OCP		5% + 0.5A
	Activation Time		< 80ms when maximum output rating
Tracking Accuracy		0.1% + 1mV	
Output Voltage Overshoot & Undershoot	Power Switch ON/OFF		No overshoot, undershoot : ≤ -0.8V
	Voltage Output Setting		No overshoot, No undershoot
Remote Interface		GPIO(IEEE-488.2) Option , RS232C Standard	
Programming Language		SCPI(Standard Commands for Programmable Instruments)	
Command Processing Time (Average of GPIB Interface)	Apply	Setting	28ms
		Query	32ms
	Output Setting	Voltage & Current Setting	28ms
		Voltage & Current Query	32ms
	Measurement	Voltage & Current Query	Present mode : 47ms    Buffer mode : 32ms
	The Other	Setting & Query	< 35ms
State Storage Memory		Ten user-configurable(voltage,current,OVP & OCP level)stored states	
Remote Sensing Capability	Voltage Drop		Up to 1V per each lead
	Load Regulation		Add 5 mV to spec for each 1-volt change in the + output lead due to load current changes.
	Load Voltage		Subtract voltage drop in load leads from specified output voltage atting.
Operation Temperature		0℃ ~ 40℃ for full rated output. At higher temperatures the output current is derated linearly to 50% at 55℃ maximum temperature	
Cooling		Isolation DC FAN	
Output Terminal Isolated (maximum, from chassis ground)		±30V output is ±60 Vdc when connecting shorting conductors without insulation to the (+)output to the (+)sense and the (-)output and the (-)sense terminals	
AC Input Ratings	Standard	220V ± 10%    50~60Hz	
		110V ± 10%    50~60Hz	
	Option	115V ± 10%    50~60Hz	
		230V ± 10%    50~60Hz	
Calibration Interval	Precision	6 month	
	Recommended	1 year	
Dimensions (19-inch 3U Standard)	Excepted the bumper	213mm(W) * 133mm(H) * 420mm(D)	
	Included the bumper	226mm(W) * 147mm(H) * 420mm(D)	
Maximum Input Power(full load)		271W	
Weight	Net weight		7kg
	Gross weight		8.5kg