

SPECIFICATIONS

Programmable DC Power Supply

MODEL : OPE-5080DI



Parameter		Specifications	
Output rating(@0°C ~ 40°C)	Channel 1	0 to 50V	/ 0 to 80A
	Channel 2	0 to 50V	/ 0 to 80A
Output WATT		8000W	
Programming Accuracy (@25°C ±5°C)±(%of output + offset)	Voltage	0.2%+333.3mV	
	Current	0.2%+400.0mA	
Readback Accuracy (@25°C ±5°C)±(%of output + offset)	Voltage	0.2%+333.3mV	
	Current	0.2%+400.0mA	
Ripple and Noise(20Hz to 20MHz)	Voltage	≤ 3mVp-p	
	Current	≤ 20mArms	
Load Regulation (@25°C ±5°C)±(%of output + offset)	Voltage	0.01%+6.7mV	
	Current	0.01%+8.0mA	
Line Regulation (@25°C ±5°C)±(%of output + offset)	Voltage	0.01%+6.7mV	
	Current	0.01%+8.0mA	
Resolution	Programming/Readback	≤12.5mV	/ ≤32.0mA
	Display Meter	100mV	/ 100mA
Temperature Coefficient ±(%of output + offset)	Voltage	0.02%+6.7mV	
	After a 30-minute warm-up	0.05%+32.0mA	
Stability ±(%of output + offset)	Voltage	0.1%+8.3mV	
	After a 1 hour warm-up	0.2%+40.0mA	
Transient Response Time		Less than 50μs for output to recover to within 50mV following a change in output current from full load to half load or vice versa	
Voltage Programming Speed (10% ~ 90%)	No load	Rising time	≤ 120ms
		Falling time	≤3.6s
	Half load	Rising time	≤ 120ms
		Falling time	≤ 15ms
Output Voltage Overshoot & Undershoot	Power Switch ON/OFF		No overshoot, undershoot : ≤0V ~ ≥ -0.3V
	Voltage Output Setting		No overshoot, No undershoot
Remote Interface		RS232C Standard (RS485 Option)	
Programming Language		SCPI(Standard Commands for Programmable Instruments)	
Command Processing Average Time (@19200bps)	Output Setting	Voltage & Current Setting	10ms
		Voltage & Current Query	12ms
	Measurement	Voltage & Current Query	15ms
	The Other	Setting & Query	32ms
State Storage Memory		Five user-configurable(voltage,current)stored states	
Operation Temperature Range		0°C ~ 40°C for full rated output. At higher temperatures the output current is derated linearly to 50% at 55°C maximum temperature	
Cooling		Isolation AC FAN	
Output Terminal Isolated (maximum, from chassis ground)		±30V output is ±60 Vdc when connecting shorting conductors without insulation to the (+)output to the (+)sense and the (-)output and the (-)sense terminals	
AC Input Ratings	Standard	220V ± 10% 50~60Hz	
	Option	100V ± 10% 50~60Hz 230V ± 10% 50~60Hz	
Calibration Interval	Recommended	1 year	
Dimensions (19-inch * 18U Standard Rack Case)		600mm(W) * 1000mm(H) * 750mm(D)	
Maximum Input Power(full load)		20611.3W	
Weight	Net weight	120kg	
	Gross weight	121.2kg	

※ 주문자 사양 모델은 spec변경이 이루어질 수 있습니다.