

SPECIFICATIONS

Programmable DC Power Supply

MODEL : OPE-5001S



ODA

TECHNOLOGIES
www.odacore.com

Parameter			Specifications	
Output rating(@0℃ ~ 40℃)			0 to 500V / 0 to 1A	
Output WATT			500W	
Programming Accuracy (@25℃ ±5℃)±(%of output + offset)	Voltage		0.2% + 900mV	
	Current		0.2% + 15mA	
Readback Accuracy (@25℃ ±5℃)±(%of output + offset)	Voltage		0.2% + 900mV	
	Current		0.2% + 15mA	
Ripple and Noise(20Hz to 20MHz)	Voltage		≤ 0.01% _{mVrms}	
	Current		≤ 3mA _{rms}	
Load Regulation (@25℃ ±5℃)±(%of output + offset)	Voltage		0.01% + 150mV	
	Current		0.01% + 1mA	
Line Regulation (@25℃ ±5℃)±(%of output + offset)	Voltage		0.01% + 150mV	
	Current		0.01% + 1mA	
Resolution	Programming/Readback		≤ 150mV / ≤ 0.5mA	
	Display Meter		1V(3-DIGIT) / 10mA(3-DIGIT)	
Temperature Coefficient ±(%of output + offset) After a 30-minute warm-up	Voltage		0.02% + 30mV	
	Current		0.02% + 3mA	
Stability ±(%of output + offset) After a 1 hour warm-up	Voltage		0.1% + 40mV	
	Current		0.2% + 3mA	
Transient Response Time			Less than 50μs for output to recover to within 50mV following a change in output current from full load to half load or vice versa	
Voltage Programming Speed (10% ~ 90%)	No load	Rising time	≤ 500ms	
		Falling time	≤5s	
	Half load	Rising time	≤ 500ms	
		Falling time	≤ 500ms	
Output Voltage Overshoot & Undershoot	Power Switch ON/OFF		No overshoot, undershoot : ≤0V ~ ≥ -0.3V	
	Voltage Output Setting		No overshoot, No undershoot	
Remote Interface			RS232C Standard (RS485 Option)	
Programming Language			SCPI(Standard Commands for Programmable Instruments)	
Command Processing Average Time (@19200bps)	Output Setting	Voltage & Current Setting		10ms
		Voltage & Current Query		12ms
	Measurement	Voltage & Current Query		15ms
	The Other	Setting & Query		32ms
State Storage Memory			Five user-configurable(voltage,current)stored states	
Operation Temperature Range			0℃ ~ 40℃ for full rated output. At higher temperatures the output current is derated linearly to 50% at 55℃ maximum temperature	
Cooling			Isolation AC FAN	
Output Terminal Isolated (maximum, from chassis ground)			±30V output is ±60 Vdc when connecting shorting conductors without insulation to the (+)output to the (+)sense and the (-)output and the (-)sense terminals	
AC Input Ratings	Standard		220V ± 10% 50~60Hz	
	Option		100V ± 10% 50~60Hz	
			230V ± 10% 50~60Hz	
Calibration Interval		Recommended		1 year
Dimensions		Standard		426mm(W) * 177mm(H) * 505mm(D) 19-inch 4U Standard Size
Maximum Input Power(full load)			1.32KW	
Weight	Net weight		19kg	
	Gross weight		20.5kg	

※ 주문자 사양 모델은 spec변경이 이루어질 수 있습니다.

